

Transmittance **$U_w \geq 0.83$ (W/m²K)**

Consult typology, dimensions and glass.

Acoustic insulation

Maximum glazing	54 mm
Minimum glazing	20 mm
Maximum acoustic insulation	Rw = 45 dB

Sightlines

Modern frame	75 mm
Classic frame	100 mm
Sash	83 mm

Profile Thickness

Window	1.5 mm
Door	1.5 mm

Polyamide strip length 32-39 mm**Maximum dimensions / Sash**

Width (L) = 1,500 mm

Height (H) = 2,600 mm

Consult maximum weight and dimensions according to typologies.

Maximum weight / Sash 160 kg**Certificates**

SKG Certification

**Categories achieved at test centre**

Protection against atmospheric agents.

Air permeability**(UNE-EN 12207): Class 4****Water tightness****(UNE-EN 12208): Class E1200****Wind resistance****(UNE-EN 12210): Class C5**

* Reference test 1.23 x 1.48 m / 2 sashes.

Test verified by

ALUMINIOS CORTIZO S.A.U.**Extrusion alloy**

6063 T-5

Finishes

Possibility of dual colour

Colour powder coating (RAL, mottled & rough)

According to Qualicoat >60 microns

Wood effect powder coating

According to Qualideco standard


Anodised

According to Ewma Euras / Standard Class 15 / Optionally Class 20 and 25


Opening possibilities

Inward opening: side hung, tilt & turn and bottom hung.

Outward opening: side hung.



* Classic version



* Modern version