

LATTICES

DECORATIVE LOUVRES

Louvre

Louvre type	Max. recommended free length*	A/C	B/C
Lattices (Ref. 2747)	2.0 metres	71%	44%
Decorative lattices (Ref. 2749)	1.5 metres	62%	34%
Clip lattices (Ref. 2829)	2.0 metres	100%	24%
Mini-lattices (Ref. 2785)	1.3 metres	55%	39%
Tubular louvres (Ref. 2847)	2.0 metres	76%	-
Decorative louvres (Ref. 9003)	1.0 metres	86%	-
Façade covering louvres (Ref. 500500)	-	-	-
Façade covering louvres (Ref. 770036)	-	-	-

* Depending on project specifications, it is possible to reach a longer louvre length (please, consult).

Categories achieved at test centre

Protection against atmospheric agents.

Lattice (Test reference 2.0 metres)

Mini-lattice (Test reference 1.3 metres)

Tubular louvres (Reference test 1.3 metres)

Wind load resistance

(UNE 13659): Class 6 (Max.)

Wind load resistance

(UNE 13659): Class 5

Wind load resistance

(UNE 13659): Class 6 (Max.)

Reference test 1.3 metres

Tests carried out according to UNE 1932 standard

Test verified by

ALUMINIOS CORTIZO S.A.U.

