

Transmittance **$U_{cw} \geq 0.6$ (W/m²K)**

Consult typology, dimensions and glass.

GlazingMax. 64 mm
Min. 4 mm**Inner sightlines**52 mm mullion
52 mm transom**Profile Thickness**2.1 & 3.0 mm mullion
2.1 mm transom**Thermal Break**6, 12 & 30 mm
stackable profiles**EPDM Gaskets**

Totally vulcanised corner gasket

Maximum dimensions / Sash**Hidden Top Hung**

Max. width (L)	2,500 mm	Min. width (L)	500 mm
Max. height (H)	2,500 mm	Min. height (H)	650 mm

Maximum weight / Sash

Hidden top hung	180 Kg
Fixed lights	750 Kg

Certificates

CWCT British Certification

**Categories achieved at test centre**

Protection against atmospheric agents.

Air permeability**(UNE-EN 12152):** Class AE**Water tightness****(UNE-EN 12254):** Class RE1500**Wind resistance****(UNE-EN 13116):** Passed

Design loading 2,400 Pa - Security loading 3,000 Pa

Reference test 3.00 x 3.50 m.

Test verified by

ALUMINIOS CORTIZO S.A.U.**Extrusion alloy**

6063 T-6

Finishes

Colour powder coating (RAL, mottled & rough).

According to Qualicoat >60 microns

Wood effect powder coating.

According to Qualideco standard

Anodised.

According to Ewwa Euras / Standard Class 15 / Optionally Class 20 and 25

Options for covers

Flat cover

14, 19 100 & 145 mm deep rectangular cover

34 mm deep H shape cover

85 mm deep elliptical cover

Opening possibilities

Hidden top hung

