

VIEW CRYSTAL FIT PLUS BALUSTRADE

Maximum height and options

Maximum height: 1,100 mm

Options: On slab, on slab edge, flush on slab edge and on inverted slab edge.

Glazing options

This balustrade system allows **12 glazing possibilities**: double glazing of **10, 8 or 6** joined by up to 4 polyvinyl butyrals of 0.38 mm. Tempered glass is recommended.

COMPOSITION				TYPE
10 - 1.52 - 10	10 - 1.14 - 10	10 - 0.76 - 10	10 - 0.38 - 10	LAMINATED
8 - 1.52 - 8	8 - 1.14 - 8	8 - 0.76 - 8	8 - 0.38 - 8	
6 - 1.52 - 6	6 - 1.14 - 6	6 - 0.76 - 6	6 - 0.38 - 6	

Categories achieved at test centre

Tests according to **UNE 85237, UNE 85238 and UNE 85240**, requirements established in **CTE (DB SU-1 and DB SE-AE)** and in Eurocode 1 according to **EN 1991-1-1**.

CLASSIFICATION ACCORDING TO UNE 85240: Class A-EXCELLENT

Reference test on balustrade with glass and extruded aluminium, fixed to the slab edge with (H) 1,100 X (L) 1,500 mm of total dimensions above ground level. Reference test on balustrade with glass and extruded aluminium, fixed on the slab with (H) 1,100 X (L) 1,500 mm of total dimensions above ground level.

VIEW CRYSTAL FIT PLUS

It withstands a load of up to **3.0 kN/m**. Suitable for use in zones **A, B, C, D, E and F**, as outlined in the **CTE DB SE-AE, and A, B, C, D and E**, in accordance with Eurocode 1.
Depending on the configuration.

